



<b>Model</b>	<b>LVDC45XSHE</b>
<b>Image Sensor</b>	1/3" SONY
<b>Horizontal Resolution</b>	Color 1/3" SONY 700TVL, Low Illumination, DWDR, OSD, DNR, UTC Effio-E
<b>Pixels</b>	NTSC:976(H)x494(V),PAL:976(H)x582(V )
<b>TV System</b>	PAL/NTSC
<b>IR range</b>	25M
<b>Lens</b>	2.8-12mm Motor Zoom Lens (2M Pixels)
<b>IR LED</b>	ø 5X30PCS
<b>Sync System</b>	Internal

<b>Usable Illumination</b>	0.001Lux/F2.0
<b>S/N Ratio</b>	≥115dB (AGC OFF)
<b>Gamma Correction</b>	0.45
<b>Video Out</b>	Composite Signal (1.0Vp-p, 75Ω)
<b>Scanning System</b>	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec
<b>Electronic Shutter Time</b>	Auto:PAL 1/50-1/100, 000Sec;NTSC 1/60-1/100, 000Sec
<b>Operation Temperature</b>	-10°C ~ +50°C RH95% Max
<b>Storage Temperature</b>	-20°C ~ +60°C RH95% Max
<b>White Balance</b>	Auto
<b>Power Source</b>	DC12V 350mA
<b>Dimension</b>	∅ 135x 110(H) mm
<b>Package</b>	55*42*42mm, 10PCS/CTN
<b>Weight</b>	1.2Kg

Vandalproof Dome Camera

IR LED: ∅ 5X30PCS IR range: 25M

2.8-12mm Motor Zoom Lens (2M Pixels)

Controlled by RS485

Bracket included

Size: ∅ 135x 110(H) mm

Weight: 1200g

