

KPC138ET

21 LEDs IR Camera



● FEATURES

- (1) High sensitivity in the dark environment, 0.1 Lux / F2.0, 0Lux (IR ON)
- (2) Day and night features for 24-hour surveillance
- (3) Excellent image quality
- (4) IR LED effective range reaches up to 15 meters
- (5) IP67 standard approved case

● SPECIFICATIONS*

MODEL	KPC138ET	
Pick-up Element	1/3" H.R. Color CCD image sensor	
Number of Pixels	771(H) x 492(V) <NTSC> / 753(H) x 582(V) <PAL>	
Resolution	520 TV Lines	
Min. Illumination	0.1 Lux / F2.0, 0Lux (IR ON)	
IR LED	21 units	
Effective Range	Up to 15 Meters	
S/N Ratio	More than 48dB (AGC OFF)	
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.	
Lens	f3.6mm / F2.0	f6.0mm / F2.0
Lens Angle	92.6°	54°
IRIS Mode	AES	
White Balance	ATW	
Video Output	1.0 Vp-p composite, 75Ω	
Power Source (±10%)	DC12V	
Current Consumption (±10%)	70mA (IR OFF), 270mA (IR ON)	
Dimensions (mm)**	140.19(L) x 55.2(W) x 79.58(H)	
IP Rating	IP67	

* The specifications are subject to change without notice.

** Dimensional Tolerance: ± 5mm

Good Sensitivity in Low Illumination

KPC13x Series



Conventional



True Color

KPC13x Series



Conventional

